



BEST AVAILABLE COPY

DECLARATION

I, the undersigned Margareta Backen, technical translator, of Bellevuevägen 46, Malmö, Sweden, do hereby declare that I am conversant with the English and Swedish languages and am a competent translator thereof, and I further declare that to the best of my knowledge and belief the following is a true and complete translation made by me of the Swedish Patent Application No. 9900908-6 filed on the 12th of March 1999 by Spectronic AB, Helsingborg, Sweden.

Signed this 10th day of January 2006

Margareta Backen

PRV

THE SWEDISH PATENT AND REGISTRATION OFFICE
Patent Department

Certificate

This is to certify that the annexed documents are true copies of the documents originally filed with the Swedish Patent and Registration Office in the following Application.

(Seal of
the Patent
Office)

Applicant(s)

Spectronic AB, Helsingborg SE

Patent Application No. 9900908-6

Filing Date 12 March 1999

Stockholm, 25 September 2001

For the Patent and Registration Office

Christina Vångborg
Christina Vångborg

Fee SEK 170

**THE PATENT AND
REGISTRATION OFFICE
SWEDEN**

Postal address

Box 5055

S-102 42 STOCKHOLM

Telephone

+46 8 782 25 00

08 782 25 00

Telex

17978

Telecopier

+46 8 666 02 86

08 666 02 86



HANDHELD OR POCKET-SIZED ELECTRONIC APPARATUS AND HAND-
CONTROLLED INPUT DEVICE

Technical Field

The present invention relates to a handheld or pocket-sized electronic apparatus, such as a mobile telephone, a handheld computer, etc., comprising a display unit and a touch surface that is position-sensitive in two directions for control of the apparatus. The invention also relates to a hand-controlled input device of touchpad type for use in such handheld electronic apparatus to provide a touch surface.

10

The invention has been developed especially for, and will be described in conjunction with, a combined mobile telephone and web browser, but is generally applicable to all types of handheld electronic apparatus where it is preferred to eliminate or reduce the number of conventional alphanumeric keyboards, individual physical function keys, a mouse, a handheld pointer pen, etc., for entering text, controlling a cursor, activating functions, etc.

15

20 Background Art

It is known to control a handheld electronic apparatus or terminal, such as a mobile telephone or a handheld computer, by means of a conventional physical keyboard, individual physical alphanumeric keys and function keys, a thumb-wheel or a mouse. The use of keyboard and individual buttons integrated with the apparatus itself has the drawback that they are bulky per se and that space problems arise when the number of functions increases. Both a separate alphanumeric keyboard and a mouse have the drawbacks of constituting an extra component for the user and of requiring a separate work surface.

25

30

- To alleviate these drawbacks electronic apparatus have been developed that can be at least partially controlled by means of a touchscreen and/or a touchpanel/touchpad.
- 5 These input devices are available in analog or digital embodiments. Using a finger and/or a separate, handheld instrument - often termed "pen" - the user can select a point on the touch surface of the touchscreen or touch-
- 10 panel for the purpose of selecting a corresponding point on the display area of the display unit. The user can thus activate various functions, such as "virtual" buttons for entering text, dialling numbers, activating functions, etc. Movement of a finger across the touch
- 15 surface can result in a corresponding movement of a cursor across the display area of the display unit. However, no cursor need exist and instead the virtual function keys may be illuminated, for instance, when corresponding areas on the display area are activated.
- 20 A touchscreen is characterised in that it is transparent and entirely or partially covers the display area of the display unit. The user presses or clicks directly on the touch surface with his finger or with a pen, at the virtual buttons or fields indicated by the display unit, and
- 25 no movable cursor is therefore necessary. A touchpanel or touchpad is characterised in that it does not coincide with the display area and is often used to control some form of cursor across the display area.
- 30 It is also known to make touchscreens and touchpads sensitive to the degree of pressure so that, by pressing sufficiently hard on the touch surface, a user can activate, i.e. "click on", a selected button or function.
- 35 Known touchscreens and touchpads can to a certain extent alleviate the above-mentioned drawbacks of alphanumerical

keyboards, physical keys, mouse and thumb-wheel, but they entail several other problems:

- 5 1. A touchscreen impairs the contrast and resolution of the picture since it is applied in front of the display area. This problem is particularly manifest in reflective display units where the light passes twice through the touchscreen. It is particularly difficult to provide glass or plastic with the conducting layer necessary for function of the touchscreen, without the transparency of the touchscreen being impaired.
- 10 2. Another drawback with touchscreens is that a part of the display area is obscured by the user's own finger.
- 15 3. A further drawback with touchscreens and touchpads is that the positioning accuracy is limited as a result of the large dimension of the finger in relation to the touch surface, a drawback that is particularly manifest with small touch surfaces. This problem can be partially alleviated by using a separate, thin pen to replace the finger but this has the disadvantage of requiring an extra component for the user to keep track of. The drawback of poor contrast is not alleviated, however, and even a pen obscures the display area to a certain extent.
- 20 4. Another important drawback of touchscreens is that they become dirty or scratched by the finger being passed over the surface, which further impairs visibility. Placing a separate scratch protection layer on top of the touchscreen is no solution since it would further impair the contrast.
- 25
- 30
- 35

5. A general drawback with pressure-sensitive touch-
screens is that the touch surface must be flex-
ible in its depth direction and the display area
as a whole therefore becomes sensitive to exter-
nal influence.

6. A touchscreen or touchpad is normally constructed
from two layers held at a relative distance from
each other by edge spacers. A problem is that the
outer layer, constituting the touch surface, is
tensioned and is therefore stretched when press-
ed. This problem is particularly prominent when
the distance between the edge spacers is small,
and especially close to these. This also entails
the drawback that the pressure-sensitivity varies
across the touch surface.

US-A-5 729 219 (Motorola Inc.) describes a handheld pager
having a casing, a display unit arranged on the front of
the casing and a flat touch surface parallel to the dis-
play area of the display unit on the opposite, rear side
of the casing. The distance between the screen and the
parallel touch surface is equal to the thickness of the
casing. The screen and touch surface are equal in size
and movement of the user's finger across the panel from
left to right results in a corresponding left-to-right
movement of a cursor on the screen, and vice versa.
A finger movement on the touch surface results in a
cursor movement of equal distance on the screen.

Summary of the Invention

The object of the present invention is to eliminate or
at least reduce one or more of the drawbacks of known
touchscreens and touchpanels described above.

To achieve this object, a first aspect of the invention
provides a handheld or pocket-sized electronic apparatus,

such as a mobile telephone, comprising a display unit and a touch surface that is position-sensitive in a first and a second direction for control of the electronic apparatus, which apparatus is characterised in that the touch surface is arranged at the side of the display unit and is curved in the first direction to convex shape.

The term "touch surface" here means a surface on a touch-panel (of touchpad type) across which a user may pass his finger to a desired position in order to guide a cursor, for instance, across the display area of the display unit and/or to activate virtual keys shown on the display area, etc. These basic functions of a touchpanel are known per se to a person skilled in the art and need not therefore be described in further detail.

Normally the movement of a finger in the two directions of the touch surface corresponds to a positioning on the display area of the display unit in two directions at right angles to each other, preferably parallel to the direction of movement of the finger on the touch surface.

An advantage of the touch surface according to the invention being curved to convex shape in a first direction is illustrated schematically in Figures 10a and 10b. The contact area 50 between the tip of the finger 51 and the curved touch surface 52 (Fig. 10b) will be formed according to the invention by two convex surfaces instead of, as in the known technology (Fig. 10a), by one convex surface (finger tip) and one flat, uncurved touch surface. The invention greatly reduces the contact area between finger tip and touch surface, thus enabling high positioning accuracy to be achieved in the width direction of the touch surface, even with a relatively narrow, longish touch surface. This in turn makes it possible to place the touch surface completely outside the display area, in a suitable place on the apparatus. It will thus be

possible to solve, by means of the invention, the above-described problems of prior-art touchscreens as regards poor resolution and contrast, dirtying. It will also be possible to solve the problem that the display area is partly obscured by the user's finger or a pen. The display unit can be made hard and less sensitive to external influence.

Another advantage of reducing the contact area between finger and touch surface is that less force is required for the user to achieve the same force per surface unit for activation of the touch surface. This is also clear from Fig. 10b.

Another advantage of the invention is that the touch surface can be designed in such a manner that the user does not need to move his finger so much in the direction in which the surface is curved (direction of curvature). In certain cases the finger may not even have to be moved or slide over the arched surface in the direction of curvature, but just "roll" over the arched surface.

An important advantage of the invention as regards embodiments of membrane type is that a curved touch surface of a certain membrane gives less resistance to depression since the membrane forming the touch surface need not be stretched. The required activation force is thus less than with known touch surfaces. In known touch surfaces the activation force required increases the nearer one comes to the edge and this means that the accuracy is considerably less reliable as a result of deformation of the tip of the finger (see Fig. 11b). Reducing the activation force is also preferred since the foil or equivalent that forms the touch surface is subjected to less strain. These problems have meant that a long, narrow touch surface could not be obtained using known techno-

logy. This is possible with the invention, however,
thanks to the lower contact pressure.

Yet another advantage with a curved touch surface is that
5 the contact pressure will be more linear, i.e. uniform,
as opposed to the known, flat touch surfaces. With known
touch surfaces of membrane type, the contact pressure
increases the closer one gets to the edge, whereas with
the curved touch surface according to the invention the
10 contact pressure is substantially constant in the direc-
tion of curvature. This advantage of the invention is
clear from a comparison between Figures 11a and 11b
showing an input device according to the invention and
a known touchpad of membrane type, respectively.

15 In a preferred embodiment the touch surface is longer in
the second direction than in the first direction (direc-
tion of curvature), and in particular the touch surface
may be single-curved about a linear geometric axis paral-
20 lel with the second direction. In this case the position-
ing accuracy in the longitudinal direction of the touch
surface is determined by the physical extension of the
touch surface in longitudinal direction. The positioning
accuracy in longitudinal direction will therefore be
25 substantially unchanged in comparison with known flat,
uncurved touch surfaces, but since the display is not
obscured the accuracy in longitudinal direction can in
practice be increased through visual feedback via the
display, e.g. with a cursor movement.

30 According to an embodiment of the invention, which is
preferred from an ergonomical point of view, the display
unit is arranged on a front side of the apparatus and the
curved touch surface is arranged wholly or partly on an
35 edge side of the apparatus. If the curved touch surface
runs, for instance, along the right edge side of the
apparatus and the user holds the apparatus in his right

hand, palm oriented towards the rear side of the apparatus, the user can operate the apparatus by moving his thumb along and across the curved touch surface on the right edge side.

5

According to a particularly preferred embodiment the curved touch surface is arranged on the side edge of the apparatus. In this embodiment the touch surface has two parallel longitudinal edges between which the curved touch surface runs, and which longitudinal edges are united with an edge each on the front side and rear side, respectively, of the apparatus. The advantage of this embodiment is that substantially the whole of the front side can be used for the display unit and the display unit can extend maximally out to the longitudinal edges of the front side.

According to another embodiment, the curved touch surface can be wholly or partly arranged on a front side of the apparatus at the side of the display unit. This embodiment can be advantageous if one wants to "click" on the touch surface in the "right direction" in the thickness direction of the apparatus.

25 The touch surface has preferably greater extension in its longitudinal direction than transversely. In particular the breadth of the touch surface in the direction of curvature can be made considerably smaller than the equivalent dimension of the display area of the display unit.

30 The desired ratio between a finger movement on the touch surface and a resultant movement on the display area can be achieved in a manner known to one skilled in the art. In particular such a ratio can be considerably greater for movement in the transverse direction of the touch surface. The ratio in longitudinal direction may be 1:1, for instance, so that a selected position in the longitudinal direction of the touch surface corresponds to

a position in the longitudinal direction of the display area lying exactly opposite the position on the touch surface, thereby giving good visual feedback to the user.

- 5 The touch surface need not, but may be, approximately the same length as the corresponding dimension on the display area of the display. Alternatively the touch surface may be somewhat longer than the corresponding dimension of the display area.

10

The touch surface may be divided in the second direction into two or more areas or fields. The division may be made by constructional means and/or logical means, i.e. solely software-controlled. Division by constructional

- 15 means might be achieved by means of electrically separated fields that may be produced in one and the same input device with a common touch surface. Two adjacent fields divided by constructional means can, however, be used as a single logically coherent field. A logical division can
20 be achieved with software indicating different pressure surfaces or fields on the touch surface via the display unit.

- In general only one position at a time shall be activated
25 on a touch surface, or for each field if the touch surface is divided by constructional means into fields as above.

- In one embodiment the touch surface comprises an upper
30 part and a lower part, of which only the upper part - normally controlled by the thumb - is active when the apparatus is held in the user's hand. This avoids the lower part of the touch surface being accidentally activated by the user's palm. The lower part of the touch
35 surface may be used, for instance, for direct control of function buttons in a list, by pressing the correct longitudinal position on the lower part of the touch sur-

single-curved about a linear geometric axis parallel with the second direction. The touch surface can be formed of a convex outside of an outer foil which is resiliently clamped at the opposite side edges to convex shape. The

5 input device may also comprise a curved inner foil arranged inside and spaced from the outer foil. The inner foil may be arranged over an arched base, and preferably secured to this base. To achieve the necessary distance the outer foil may have a greater curvature than the sur-

10 face against which the outer foil shall be depressed, e.g. the outer side of a curved inner foil. This can be achieved, for example, by making the outer foil somewhat wider in transverse direction and clamping the longitudinal sides of the foils together at the longitudinal

15 edges of the touch surface. The outer foil will then rise resiliently from the inner foil in order to maintain a distance between the foils, which distance can be reduced by the user pressing his finger on the touch surface. Naturally the distance between the foils can also be

20 influenced by suitable spacers, particularly at the edges.

The outer and inner foils can be made from one and the same foil which is provided with the necessary layers and

25 conductors and thereafter folded around a fold line in order to form both the inner and the outer foil.

The input device with a curved touch surface in accordance with the invention allows for a narrow touch surface on a limited area. This is not possible with conventional, flat touchpanels. A conventional flat touchpanel has spacer elements requiring the panel to be protected from being touched over a distance of about 2 mm from the spacer elements since a conventional touchpanel is based

30 on the outer foil being stretched down to the inner foil upon activation. Without this safety margin there is a risk of the outer foil being deformed and/or becoming

35

detached from the spacer. Thus, part of the available area is lost, that is to say the area taken up by the spacer elements (in one direction at least $2 + 2$ mm) and also the safety margin of $2 + 2$ mm (see Fig. 11b). An
5 inactive area of 8 mm is naturally unacceptable if the panel is to be made as narrow as 10 mm, for instance. This problem is eliminated in the input device in accordance with the invention since no stretching occurs.

10 Furthermore, conventional touchpanels cannot be bent to convex form and still retain their function, because the distance to the outer foil will be incorrect.

Thus, in accordance with the invention, a compact, hand-
15 held electronic apparatus can be produced, such as a mobile telephone, with a display area which covers essentially the entire front side of the apparatus. This is possible since entering data does not require operation of a separate keyboard or physical buttons on the front
20 side of the apparatus. Instead, the apparatus in accordance with the invention is provided with one or more pressure-sensitive touch surfaces on and/or adjacent the edge sides of the apparatus, beside the display area. The available space beside such a large display area, how-
25 ever, is limited. If the touch surface in its entirety is to be arranged on the side edge of the apparatus, the touch surface may not be wider than the thickness of the apparatus, which may be in the order of 10 mm or less. The length of the touch surface is normally not critical
30 since the whole length of the apparatus is available. Pressing with a finger, particularly a thumb, on a narrow and flat oblong surface with a width of only 10 mm does not offer acceptable accuracy, as well as demanding too much force. However, this problem is solved in accordance
35 with the invention by the touch surface being given a convex shape in its transverse direction.

Description of the Drawings

- Figure 1 is a view in perspective of the front side of a mobile telephone, constituting one embodiment of a handheld electronic apparatus in accordance with the invention,
- Figure 2 shows the rear of the mobile telephone in Figure 1,
- Figure 3 is a side view of an inner chassis or frame of the mobile telephone in Figure 1,
- Figure 4 is a top view of the chassis in Figure 3,
- Figure 5 is a cross section through an input device shown in Fig. 4,
- Figure 6 is an enlargement of part of the input device shown in Figure 5,
- Figure 7 illustrates a method for producing an input device in accordance with the invention,
- Figure 8 illustrates a method for producing a second input device in accordance with the invention,
- Figure 9 is a schematic cross sectional view, not drawn to scale, of the input devices in Figures 8 and 9.
- Figure 10 illustrates schematically one aspect of the function of the invention,
- Figure 11 illustrates schematically a second aspect of the function of the invention,

Description of the Preferred Embodiments

A combined mobile telephone/web browser 1 shown in Figures 1 and 2 has a front side 2, a rear side 3, two opposite edge sides 4, 5, a bottom side 6 and a top side 7. The mobile telephone 1 is provided with communication means comprising an aerial 8, a microphone 9, a loud-speaker 10 and electronic transceiver circuits, not shown, arranged internally in the apparatus. The latter circuits may be of conventional type and are therefore not described further in detail. A display unit with a rectangular display area 12 is arranged on the front side

2 and a battery compartment 13 is arranged on the rear side 3. Unlike conventional mobile telephones, the display area 12 of the display unit takes up almost the entire front side 2. Only two small areas above and below the display area 12 are free for the loudspeaker 10 and the microphone 9, respectively. The mobile telephone/web browser 1 also comprises electronic circuits (not shown) necessary for various functions of the apparatus, such as processors, display drive units, memory circuits, etc., which are known to those skilled in the art and will not therefore be described in detail. Figure 2 also shows a camera 14 on the rear side 3, which is in no way necessary for the invention and is therefore not described in further detail.

15 The mobile telephone 1 is provided with two elongate input devices 20, 21 of "touchpad" type, controlled by the fingers, extending along each edge side 4 and 5, respectively, for controlling the mobile telephone 1 and its display unit. This embodiment comprises two input devices but a simpler embodiment may have only one input device, preferably the input device 20 on the right edge side 4 for control with the thumb of the right hand.

25 Characteristic of the mobile telephone 1 in this embodiment is that it lacks other input devices in the form of physical keys, thumb-wheel, etc. All activation and control on the part of the user can be performed with the aid of the input devices 20, 21.

30 The basic design of the right input device 20 will now be described. The design is substantially the same as for the left input device 21. As shown in Figures 5 and 6 the input device 20, observed from the inside, comprises the following three basic components: (i) an elongate base 22 with an arched surface 23 and a rear side 24, (ii) an inner foil 25 and (iii) an outer foil 26. The exterior of

the outer foil 26 may form the curved touch surface but in a preferred embodiment it is covered by a flexible outer casing as described below. Figures 3 and 4 show the inner chassis 11 of the mobile telephone 1 with the input device in place, but without outer casing or battery.

The base 22 in the embodiment shown is approximately 127 mm long and 13.5 mm wide, these dimensions fitting the dimensions of the side edge 4 of the apparatus. The curved surface 23 has a radius of curvature of approximately 1 cm. The inner foil 25 and outer foil 26 in this embodiment are made of PET plastic foil 0.05 mm in thickness, but other materials and thicknesses can naturally be used. The area of the inner foil 25 coincides with the size of the curved surface 23 of the base 22 and is secured to the curved surface 23 of the base by means of a layer 27 of binder, such as self-adhesive tape. The flat rear side 24 of the base 22 is attached in suitable manner to the edge side 4. In an alternative embodiment the base 23 may instead be integrated with, i.e. constructed in one piece with the chassis 11 shown in Figures 3 and 4.

The outer foil 26 is electrically insulated from the inner foil 25 at both long edges 26 by means of strip-like layers of insulating varnish 28 and adhesive. The outer foil 26 is somewhat broader (in the present case approximately 13.9 mm) than the inner foil 25 so that, by being clamped at its longitudinal edges at the designations 29, it is caused to assume a sharper curvature than the inner foil 25. The result is that the outer foil 26 is raised from the inner foil 25 and that a small gap Δ in the order of 0.25 mm is formed between the inner and outer foils at the mid-position P1 and in the order of 0.05 mm at the edge positions P2. This gap Δ is thus achieved without the use of any separate spacer elements. Since the outer foil 26 is resilient the gap Δ can be

momentarily eliminated at a point where the user temporarily places a finger. The outer foil 26 need not be stretched in order to make contact with the inner foil 25. The only inactive areas of the touch surface are those above the insulation varnish 28. When the user releases the finger pressure the gap Δ will be restored as a result of the resilience of the outer foil 26.

For resistive registering of the co-ordinates for a depressed position on the touch surface of the input device, the inner foil 25 and the outer foil 26 are in this embodiment provided in known manner with resistive layers, provided with electrodes, on the sides facing each other, which resistive layers, for instance, are of a graphic mixture.

A method for producing the input devices 20 and 21 will now be described. Reference is first made to Figures 7 and 9 in combination, which illustrate schematically the production of the left input device 21 of the mobile telephone. The cross section in Figure 9 is greatly reduced in horizontal direction and is enlarged in vertical direction. The left input device 20 is intended primarily for use when the apparatus 1 is in horizontal position, e.g. during use as a web browser. It is therefore sufficient for the left input device 20 to be one single input device and not divided into two fields in its longitudinal direction like the right input device 21, as will be described further below.

The upper part of Figure 7 shows a coherent foil intended to be folded about a longitudinal fold line L in order to form the inner foil 25 and the outer foil 26. Thus, in the finished input device 21, the inner and outer foils are joined at the fold line L (see Figure 6), whereas the outer foil 26 protrudes slightly outside the inner foil 25 at the opposite edge. The lower part of Figure 7 shows

a printed wiring and electrode pattern 30 of silver, for instance, which is applied directly on the unfolded foil 25, 26. The pattern 30 comprises two relatively long x-electrodes 31, located parallel with each other, on the outer foil side 26 and two relatively short y-electrodes 32, located parallel with each other, on the inner foil side 25, for determining the x-position and y-position, respectively, of a point where the user presses with his finger. The electrodes 31 and 32 are connected via conductors to connection terminals 33. Two layers 34, 35 of insulating varnish, Dupont 5018G, are applied on the pattern 30. Two resistive graphic layers 36, 37, respectively, are then applied on these layers. The graphic layers are electrically connected to the electrodes 31, 32, respectively, as shown in Figure 9, and are insulated from each other. Their width is considerably greater than is indicated in Figure 9 and corresponds to the extension of the touch surface in transverse direction. When the graphic layers 36, 37 are applied they will come into direct electrical contact with respective electrodes 31 and 32, as shown schematically by thin lines in Figure 9. Finally the insulating layers 28 are applied on the graphic layers 36 and 37 to keep them insulated from each other at their longitudinal edges where the foil is folded.

The foils 25, 26 with the applied layers and wiring pattern, are then folded around the fold line L so that one foil part 26 is placed on top of the other foil part 25 in order to form the finished input device 20, ready for connection to the drive electronics via connection terminals 33. In the embodiment shown the foils are provided along the fold line L with a number of through-slots 60 and intermediate connections 61 that act as "hinges" during folding and which keep the two foils together. The wiring pattern 30 runs at the outer connections 62.

An advantage of the construction described above is that the resistive layers 36, 37 are arranged like a motor-way spaced above the electrodes and conductors, thereby greatly saving space. No separate spacers are required
5 and the construction as a whole is cost-efficient and advantageous from the production aspect.

The right input device 21 is produced in much the same way except that its area is divided in its longitudinal
10 direction into an upper part 21-1 and a lower part 21-2, as indicated in Figure 8. Each part has two x-electrodes 31 and two y-electrodes 32. Otherwise the manufacturing method is the same. This division allows the lower part
15 21-2 to be inactivated by suitable software if it is desired to avoid involuntary activation with the palm of the right hand while the upper part 21-1 is being controlled by the thumb of the right hand.

20 Implementation of the positioning function of the input devices 20, 21 is known per se and need not be described in detail. The resistive layers 36, 37 can be put under voltage by necessary drive circuits alternately with a
25 suitable frequency. When the user presses together the graphic layers 36, 37 at a certain point, the location of the point is determined in two directions by high-ohmic measurement on the layer temporarily not under voltage. This position determining is then used to control
30 the display unit 11, e.g. to control a cursor, for selection of virtual buttons, etc., shown on the display unit 11. The function of the input devices 20, 21 in particular can be application-controlled.

35 The arrangement is preferably also made sensitive to the magnitude of the pressure, this being achieved by resistively determining the magnitude of the depressed effective contact area between the resistive layers 36, 37.

- When the contact pressure increases, the contact area increases since the finger is deformed. The transition resistance thus falls and a measurement is obtained of how hard one is pressing. This can be used to activate various functions when the correct position has been selected in x and y direction. A click function can also be obtained, as described, with a third foil inside the inner foil (not shown).
- 10 As an alternative to the embodiment described above the input devices 20, 21 can be implemented with a matrix system comprising a set of intersecting conductors, e.g. columns on one foil and rows on the other. The depressed position can easily be determined by a scanning process.
- 15 As mentioned above, the display unit can be made relatively insensitive to jolts since no flexible touch surface covering the display area 12 is necessary. To make the apparatus even better able to withstand external influence such as moisture and blows, the chassis 11 of the apparatus 1, with the exception of the display area 12 and battery lid 13, may be covered by a suitable waterproof and/or shock absorbing material, such as a shell of elastomeric material. This shell may particularly cover also the input devices 20, 21 and must then be flexible so as not to affect their function. The surface of this shell may be provided with a pattern that can be physically felt above the touch surface of the input devices 20, 21, such as the longitudinal ribs shown in Figures 1 and 2. Such a pattern could also be arranged directly on the exterior of the outer foil 26. This shell may also be integrated with a transparent protective foil or plate covering the display area 12. Should this transparent surface become scratched it can then easily be replaced by replacing the shell with integrated, transparent protective foil or plate.

CLAIMS

1. A handheld or pocket-sized electronic apparatus (1),
5 such as a mobile telephone, comprising a display unit
and a touch surface (20; 21) that is position-sensitive
in a first and a second direction for control of the
electronic apparatus, characterised in that
the touch surface (20; 21) is arranged at the side of the
10 display unit and is curved in the first direction to con-
vex shape.
2. An apparatus as claimed in claim 1, wherein the touch
surface (20; 21) is longer in the second direction than
15 in the first direction.
3. An apparatus as claimed in claim 1 or claim 2, where-
in the touch surface (20; 21) is single-curved about a
linear geometric axis parallel with the second direction.
20
4. An apparatus as claimed in any one of the preceding
claims, wherein the display unit is arranged on a front
side (2) of the apparatus (1) and the curved touch sur-
face (20; 21) is arranged wholly or partly on an edge
25 side (4; 5) of the apparatus (1).
5. An apparatus as claimed in claim 4, wherein the
touch surface (21; 20) is arranged in its entirety on
the side edge (4; 5) of the apparatus (1) and has two
30 parallel longitudinal edges between which the curved
touch surface (21; 20) runs and which longitudinal edges
are united with the front side (2) and the rear side (3)
respectively of the apparatus (1).
- 35 6. An apparatus as claimed in any one of claims 1-3,
wherein the display unit is arranged on a front side (2)

of the apparatus (1) and the curved touch surface (20; 21) is arranged wholly or partly on the front side (29) of the apparatus (1) at the side of the display unit (11).

5

7. An apparatus as claimed in any one of the preceding claims, wherein the display unit has a display area (12) taking up most of the front side (2) of the apparatus (1).

10

8. An apparatus as claimed in any one of the preceding claims, wherein the display unit has a display area whose extension in the direction corresponding to positioning in the first direction of the touch surface is greater than the extension of the touch surface in the first direction.

15

9. An apparatus as claimed in any one of the preceding claims, wherein the display unit has a display area (12) whose extension in the direction corresponding to positioning in the second direction of the touch surface is substantially equivalent to the extension of the touch surface in the second direction.

20

10. An apparatus as claimed in any one of the preceding claims, wherein the touch surface (21) is divided in the second direction into two or more part-surfaces (21-1, 21-2) with separate position determining.

25

11. An apparatus as claimed in any one of the preceding claims, wherein the curved touch surface (20) constitutes a first of two (20, 21) such curved touch surfaces, which touch surfaces (20, 21) are arranged on opposite sides of the display unit.

30

35

12. A hand-controlled input device (20; 21) comprising a touch surface that is position-sensitive in a first and a

second direction and over which touch surface a user is to pass a finger, and means (25, 26, 30, 36, 37) for sensing the position of the finger in said two directions on the touch surface (21; 20), c h a r a c t e r i s e d
5 in that the touch surface is curved in the first direction to convex shape.

13. An apparatus as claimed in claim 12, wherein the touch surface (20; 21) is longer in the second direction
10 than in the first direction.

14. An apparatus as claimed in claim 1 or 2, wherein the touch surface (20; 21) is single-curved about a linear geometric axis parallel with the second direction.
15

15. An input device as claimed in any one of claims 12-14, wherein the touch surface is formed by a convex outer side of a resilient outer foil (26) clamped at its longitudinal edges.
20

16. An input device as claimed in claim 15, also comprising a curved inner foil (25) arranged inside and spaced from the outer foil (26).

25 17. An input device as claimed in claim 16, wherein the outer foil (26) has greater curvature than the inner foil (25).

30 18. An input device as claimed in claim 17, wherein the outer foil (26) has greater extension in its transverse direction than the inner foil (25), so that it is brought into a relative distance from the inner foil (25) when the foils (25, 26) are clamped to the convex form along their opposite longitudinal edges.

ABSTRACT


The invention relates to a handheld or pocket-sized electronic apparatus (1), such as a mobile telephone, comprising a display unit (12) and a touch surface (20; 21) that is position-sensitive in a first and a second direction for control of the electronic apparatus. The touch surface (20; 21) is arranged at the side of the display unit (12) and is curved in the first direction to convex shape. The invention also relates to an input device with a touch surface thus curved. The invention makes it possible to place a relatively narrow touch surface at the side of a display unit and at the same time achieve good precision accuracy.

Drawing for publication: Figure 1.




Received in the Patent Office
on 12 March 1999



Fig 1





Received in the Patent Office
on 12 March 1999









Fig 7





Fig 8







Fig 10a






Fig 10b



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)